




White Pearl



Sky Pearl



Sage Pearl



Amber Pearl



Alpine White




Snow Flurry




Latte




Forest Fern




Ocean Grass




Pearl Grey




Fogbound




Gotham Grey



Cobalt Ice




Sapphire Snow



Tuscan Sunset



Moroccan Red



Confetti

STANDARD COLOR COLLECTION

Custom color development is available for projects that meet production criteria; contact IceStone LLC to begin your custom color project.

Note: There may be some difference from printed material to actual product. Please visit icestoneusa.com to order samples.



Style + Sustainability

Made from 100% post-industrial recycled glass and cement, IceStone is the MOST sustainable, responsibly made, eco-friendly countertop on the market. Since IceStone's inception in 2003, we have operated under a triple bottom line: People, Planet, and Profit. IceStone has won several accolades for sustainability and is also a founding B Corp member.

NEW IceStone incorporates a formula providing our surface with permanent protection (see the benefits of NEW IceStone below). Whether using IceStone for countertops, vanities, conference tables, reception or retail exchange areas, IceStone will help you realize your vision elegantly and responsibly. To date, IceStone has diverted over 17 million pounds of glass from landfills.

- 75% recycled glass by weight
- Superior stain resistance
- Cradle to Cradle Certified Silver & bronze
- Heat resistance
- Recycled content and material health disclosure help contribute to LEED points
- NSF 51 Certified for splash zone applications in food-related establishments
- No petrochemicals or plastic resins
- UV stability for exterior applications
- No yearly maintenance
- Recycled content that reduces its carbon footprint



DISCOVER WHAT'S BENEATH THE SURFACE



Specifications

Slab Size: 52.5" x 96.5" x 1.25" nominal (35 sq. ft.)

Weight: 570 lbs/slab, 16.3 lbs/sq. ft.

Property	Test Standard	IceStone Results
Compressive Strength	ASTM C-109	13,000 -16,000 psi
Flexural Strength	ASTM C-203	890 psi
Specific Gravity	ASTM C-97	2.31 g/cm3
Porosity/Absorption	ASTM C-642	0.18% unsealed
Chemical Durability	ASTM C-1260 for ASR reactivity	0.49% 300 cycles
Freeze Thaw	ASTM C-666	0.05%
Fire Rating	ASTM E-84	Class 1(A) Flame spread index 0 Fuel contribution 0 Smoke density index 0
Coefficient of Static Friction	ASTM C-1028	0.69 polished dry 0.61 polished wet 0.71 honed dry 0.62 honed wet 0.85 sandblasted dry 0.77 sandblasted wet
Food Equipment Materials	NSF 51	Certified

Installation + Maintenance

IceStone surfaces are fabricated, installed, and maintained much like natural stone. Please refer to the IceStone Fabrication Guidelines and Care & Maintenance Guidelines for more details.